

# Tattoo<sup>2</sup>

Go badge, print yourself!



Color &  
Monochrome  
Thermal  
Transfer



300 dpi



Single-sided



100 cards



0.25-0.76 mm  
(10-30 mil)



1 year

**evolIS**

[www.evolis.com](http://www.evolis.com)

**Compact size, ease of use, core features and cost efficiency. Tattoo<sup>2</sup> is the best deal for printing plastic cards on a small scale and for mobile applications.**

In a few seconds, **Tattoo<sup>2</sup>** personalizes in monochrome or colour your pre-printed or blank plastic cards.

With a 300 dpi standard resolution and 'near-to-edge' printing, Tattoo prints pictures, texts, barcodes and logos as required.

**Tattoo<sup>2</sup>** is a flexible solution which offers a dual card-feeding mode. Cards can be loaded automatically thanks to the 100-card feeder but you can also use the manual loading mode for on-demand delivery.

It also features a detachable output hopper to collect printed cards.

Sleek and with a contemporary look, **Tattoo<sup>2</sup>** is today the most compact plastic card printer in its category.

It squeezes into any location: offices, reception desks, and even shop counters.

**Tattoo<sup>2</sup>** fully addresses the specific needs of small organizations that print badges in low volume or just once in a while: sport clubs, SMEs, retail outlets, schools, libraries and local authorities

It is ideal for membership cards, subscription and loyalty cards, badges for visitors and employees and much more.

Go badge, print yourself!

### GENERAL SPECIFICATIONS

- Color printing module
- 300 dpi print head (11.8 dots/mm)
- USB connection
- 16 MB RAM
- Detachable feeder with a capacity of 100 cards (0.76 mm or 30 mil)
- Detachable output hopper with a capacity of 15 cards (0.76 mm or 30 mil)
- 1-Button and 4-LED control panel
- Available in Fire red color
- Automatic card thickness adjustment

### CARD LOADING MODES

- Automatic with feeder and/or hand-feed

### PRINT MODES

- Color dye sublimation and monochrome thermal transfer
- Integrated ribbon saver for monochrome printing

### PRINTING SPEED

Personalization throughput will depend on card design and printer settings

- Color (YMCKO): 40 sec/card<sup>1</sup>
- Monochrome: 7 sec/card<sup>1</sup>

### SUPPORTED PLATFORMS

- Windows™ XP, Server 2003 and Vista 32 & 64 bits

### SUPPLIED SOFTWARE

- eMedia Trial - 30 days evaluation

### RIBBON TYPES

- 5-panel YMCKO color ribbon - up to 100 cards/roll
- Monochrome ribbons - Up to 600 cards/roll: available in black, red, green and blue - Up to 500 cards/roll: available in white, gold and silver
- BlackWAX monochrome ribbon (for ABS & special varnished plastic cards) - up to 600 cards/roll


### OPTIONS / ACCESSORIES

- 100-card additional feeder
- Cleaning kits

### WARRANTY

Use Evolis Genuine products for best performance and extended lifespan of your printer

- Printer, print head: 1 year warranty, unlimited number of passes<sup>2</sup>



#### Card types

#### Card format

#### Card thickness

#### Card feeder capacity

#### Card output hopper capacity

#### Printer size

#### Printer weight

#### Connections

#### Electrical

#### Environmental

- All PVC, Composite PVC cards, PET, ABS<sup>1</sup> & varnished<sup>1</sup> cards
- ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 3.375" x 2.125")
- From 0.25 mm (10 mil)<sup>3</sup> to 0.76 mm (30 mil)
- 100 cards (0.76 mm - 30 mil), 300 cards (0.25 mm - 10 mil)
- 15 cards (0.76 mm - 30 mil), 45 cards (0.25 mm - 10 mil)
- Height: 166 mm (6.53") - Length: 290 mm (11.42") / 368 mm (14.49") with the detachable hopper
- Width: 187 mm (7.36")
- 2.4 Kg (5.3 Lbs)
- USB (Cable supplied)
- Power supply: 110-230 Volts AC, 1,8 A, 60-50 Hertz
- Printer: 24 Volts DC, 3 A
- Min/Max operating temperature: 15° / 30°C (59° / 86° F)
- Humidity: 20% to 65% non-condensing
- Min/Max storage temperature: -5° / +70°C (23° / 158° F)
- Storage humidity: 20% to 70% non-condensing
- Operating ventilation: free air

1. Under specific conditions

2. Subject to observance of specific conditions and use of Evolis Genuine Consumables

3. 10 mil cards must be used only for monochrome printings



**evolis**

#### EUROPE, MIDDLE EAST, AFRICA

##### Evolis Card Printer

14, avenue de la Fontaine  
Z.I. Angers-Beaucouzé  
49070 Beaucouzé - France  
Tel: +33 (0) 241 367 606  
Fax: +33 (0) 241 367 612  
info@evolis.com

#### AMERICAS

##### Evolis Inc.

1835 South Perimeter Road  
Suite 190 - Fort Lauderdale  
FL 33309 - USA  
Tel: (954) 491-9898  
Fax: (954) 491-5140  
evolisinc@evolis.com

#### ASIA PACIFIC

##### Evolis Asia Pte Ltd

120 Lower Delta Road  
#13-12 Cendex Centre  
Singapore 169208  
Tel: +65 6377 9731  
Fax: +65 6278 7002  
evolisasia@evolis.com